



Industrie Service

Certificate No. VR2 – 1401/1 – 111 EU

The TÜV SÜD Industrie Service GmbH, test body for vapor recovery systems,
Westendstr. 199, D-80686 Munich,



certifies having conducted tests according to EN 16321-1
on the following petrol vapour recovery system:

Type of system:	Active, distributed system with mechanical proportional valve
Nozzle:	ELAFLEX ZVA Slimline 2 GRVP
Hose assembly:	ELAFLEX Conti Slimline 21/8
Proportional valve:	ELAFLEX GRVP mechanical valve integrated into the nozzle
Vapour recovery pump:	Gardner Denver Thomas, 8014-6.0

Conditions for installation and operation:
Requirements to ensure system performance in use

Maximum volumetric fuel-flow rate:	40 l/min
Maximum back pressure in petrol vapour pump outlet line with maximum vapour flow:	50 mbar
Correction factor for system settings with simulated petrol-flow of 38 l/min.:	1,13
Measured efficiency:	89 %
<i>Required efficiency by Directive 2009/126/EC</i>	85 %
Corresponding reports: "Efficiency 1401/1 Slimline 2", "System 1401/1 - 111 EU"	

The vapour recovery system corresponds to the state of the art as defined in the
"Directive 2009/126/EC".

Germany, Munich 14/07/2015

Expiration date 14/07/2017



Test Body for Vapor Recovery Systems

Peter Szalata

Peter Szalata